



## Technical data

## RRL 200

Engine	Deutz TCD 3.6 L4 Stage V
--------	--------------------------

Cylinders	R-4
-----------	-----

Capacity	3.6 l
----------	-------

Rated power	143 hp / 105 kW
-------------	-----------------

Rated speed	2,300 rpm – limited to max. 1,600 rpm
-------------	---------------------------------------

Maximum torque at 1,600 rpm	550 Nm
-----------------------------	--------

Fuel-tank capacity	Approx. 320 l
--------------------	---------------

AdBlue-tank capacity	Approx. 19 l
----------------------	--------------

## Chassis

Axles	2 braked stub axles
-------	---------------------

Track width	2.42 m
-------------	--------

Tyres	540/65 R30 – Tyre pressure 2.5 bar
-------	------------------------------------

Brakes	Compressed-air brake system
--------	-----------------------------

Towing connection	40 mm eyelet
-------------------	--------------

Supporting legs	Front and rear, hydraulically foldable
-----------------	--

## Bunker

Bunkercapacity	9 m <sup>3</sup> (hydraulically foldable bunker walls)
----------------	--

Scraper floor	Screw-on, wear-resistant guide rails 2 round steel chains with automatic speed regulation by metering flap
---------------	---

Control	Teleradio radio remote control for operating all functions
---------	--

Cleaning	Can be equipped in different ways for sugar beet, potatoes or chicory
----------	---

Cross belt	Adjustable speed, sections: 50 mm
------------	-----------------------------------

Transfer belt	Adjustable speed, plastic carriers, sections: 50 mm
---------------	---

Safety features	Finger roller-cleaing system and stone-separating roller automatically reverses
-----------------	---

## Dimensions &amp; weights

Transport dimensions	10.62 m / 3.00 m / 3.60 m (Length / Width / Height)
----------------------	---

Transfer height / width	5.50 m / 9.50 m, up to 125° swivel angle
-------------------------	--

Transfer capacity	Approx. 200 t/h
-------------------	-----------------

Max. permissible speed	40 km/h
------------------------	---------

Tare weight	Approx. 10,5 t (1,7 t permissible supported load)
-------------	---